# SAFETY DATA SHEET RANUC<sup>®</sup> KOP-COAT Revision Date 06-Sep-2018

Version 2

### 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Product code Ramuc ULTRA PRO 2000 - 329 Royal Blue 972232900

#### **<u>1.2 Relevant identified uses of the substance or mixture and uses advised against</u>**

Recommended UsePool paintRestrictions on useRead label instructions and SDS

### 1.3 Details of the supplier of the safety data sheet

Supplier
----------

Kop-Coat, Inc. RAMUC 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

#### 1.4 Emergency telephone number

Emergency telephone number	Chemtrec: +1 703-527-3887 ex-USA
	Chemtrec: 1-800-424-9300 USA

### 2. Hazards identification

### 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910.1200

Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

#### 2.2 Label elements

Signal Word Warning

### Hazard Statements

Suspected of causing cancer Suspected of damaging fertility or the unborn child May cause respiratory irritation. May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure Flammable liquid and vapor



### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge Keep cool

### Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower IF INHALED: Remove person to fresh air and keep comfortable for breathing In case of fire: Use CO2, dry chemical, or foam to extinguish

### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep container tightly closed

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### 2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

### 2.4 Other information

Not Applicable

### **Unknown Acute Toxicity**

< 1% of the mixture consists of ingredient(s) of unknown toxicity

### 3. Composition/Information on Ingredients

### Substance

Not applicable

Chemical Name	CAS No.	Weight-%
Parachlorobenzotrifluoride	98-56-6	20 - 30
CLAY (KAOLIN)	1332-58-7	20 - 30
Xylene	1330-20-7	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Mica	12001-26-2	1 - 5
Ethylbenzene	100-41-4	1 - 5
Toluene	108-88-3	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First aid measures 4.1 Description of first-aid measures **General advice** For further assistance, contact your local Poison Control Center. Call a poison control center or doctor for treatment advice. Immediately flush with plenty of Eve contact water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Skin contact Call a poison control center or doctor for treatment advice. Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Inhalation Call a poison control center or doctor for treatment advice. Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician or poison control center immediately. Rinse mouth. Do NOT induce Ingestion vomiting. If a person vomits when lying on his back, place him in the recovery position. 4.2 Most important symptoms and effects, both acute and delayed See Section 2.2, Label Elements and/or Section 11, Toxicological effects. Symptoms 4.3 Indication of any immediate medical attention and special treatment needed There is no specific antidote for effects from overexposure to this material. Treat Notes to physician symptomatically. 5. Fire-Fighting Measures

### 5.1 Extinguishing media

### Suitable extinguishing media

Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

### 5.2 Special hazards arising from the substance or mixture

#### Special Hazard

Thermal decomposition can lead to release of irritating gases and vapors. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to areas away from work site before igniting/flashing back to vapor source.

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

### **Explosion Data**

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Yes.

### 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. Thoroughly decontaminate all protective equipment after use. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

### 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

### 6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

### 6.3 Methods and materials for containment and cleaning up

Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Dike far ahead of liquid spill for later disposal. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use non-sparking tools and equipment.

### 7. Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling	Empty containers may retain product residue or vapor. Ensure adequate ventilation. Ground and bond containers when transferring material. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.				
Hygiene measures	Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.				
7.2 Conditions for safe storage, inc	7.2 Conditions for safe storage, including any incompatibilities				
Storage Conditions	Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.				
Materials to Avoid	No materials to be especially mentioned.				

## 8. Exposure controls/personal protection

### 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Parachlorobenzotrifluo	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>
ride		TWA: 2.5 mg/m <sup>3</sup>				
98-56-6		dust				
CLAY (KAOLIN)	TWA: 2 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
1332-58-7	particulate matter	total dust	-	-	-	-
	containing no	TWA: 5 mg/m <sup>3</sup>				
	asbestos and <1%	respirable fraction				
	crystalline silica,					
	respirable fraction					
Xylene	STEL: 150 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	STEL: 150 ppm	TWA: 434 mg/m <sup>3</sup>	TWA: 434 mg/m <sup>3</sup>	STEL: 150 ppm
		_		STEL: 150 ppm	STEL: 150 ppm	
				STEL: 651 mg/m <sup>3</sup>	STEL: 651 mg/m <sup>3</sup>	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
13463-67-7		total dust	TWA: 3 mg/m <sup>3</sup>	-		-

Mica	TWA: 3 mg/m <sup>3</sup>	TWA: 20 mppcf	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
12001-26-2	respirable fraction	<1% Crystalline				
		silica				
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	TWA: 20 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 20 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>		TWA: 434 mg/m <sup>3</sup>	TWA: 434 mg/m <sup>3</sup>	
				STEL: 125 ppm	STEL: 125 ppm	
				STEL: 543 mg/m <sup>3</sup>	STEL: 543 mg/m <sup>3</sup>	
Toluene	TWA: 20 ppm	TWA: 200 ppm	TWA: 20 ppm	TWA: 50 ppm	TWA: 50 ppm	TWA: 20 ppm
108-88-3		Ceiling: 300 ppm	Adverse	TWA: 188 mg/m <sup>3</sup>	TWA: 188 mg/m <sup>3</sup>	
			reproductive effect	Skin	Skin	

### 8.2 Appropriate engineering controls

Engineering Measures	Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Ensure adequate ventilation, especially in confined areas.	
8.3 Individual protection measures	s, such as personal protective equipment	
Eye/Face Protection	Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles.	
Skin and body protection	Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Wear suitable protective clothing. Remove and wash contaminated clothing before re-use.	
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.	
Hygiene measures	See section 7 for more information	

9.1 Information on basic physical a Physical state	Liquid		
Appearance	No information available	Color	Blue
Odor	Aromatic solvent	Odor Threshold	No information available
Property	<u>Values</u>	Remarks • Methods	
pH Molting/freezing point	no data available	Not Applicable No information available	
Melting/freezing point Boiling point/boiling range	no data available	No information available	
Flash Point	39 °C / 102 °F		
Evaporation rate	< 1	Butyl acetate=1	
Flammability (solid, gas)		No information available	
Flammability Limits in Air			
upper flammability limit		No information available	
lower flammability limit		No information available	
Vapor pressure		No information available	
Vapor density		No information available	
Specific Gravity	1.407		
Water solubility		No information available	
Solubility in other solvents		No information available	
Partition coefficient		No information available	
Autoignition temperature		No information available No information available	
Decomposition temperature Viscosity, kinematic	> 21 mm2/s	No information available	
Viscosity, dynamic	> 21 111112/3	No information available	
viscosity, dynamic			
Explosive properties		No information available	
Oxidizing Properties		No information available	
<b>C</b> .			
9.2 Other information Volatile organic compounds (VOC) content	161 g/L Material VOC, 276 g/L Coa	ting VOC	
Density	11.72 lb/gal		

### 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

### **10. Stability and Reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use

### 10.2 Chemical stability

Stable under recommended storage conditions

#### 10.3 Possibility of hazardous reactions

None under normal processing.

### 10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

#### 10.5 Incompatible Materials

No materials to be especially mentioned.

### 10.6 Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. None under normal use conditions.

### **11. Toxicological information**

### 11.1 Acute toxicity

### Numerical measures of toxicity: Product Information

### The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity	< 1% of the mixture consists of ingredient(s) of unknown toxicity
Oral LD50	11,064.00 mg/kg
Dermal LD50	4,327.00 mg/kg
LC50 (Dust/Mist)	51.84 mg/l
LC50 (Vapor)	111.00 mg/l

#### Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Parachlorobenzotrifluoride 98-56-6	> 6800 mg/kg (Rat)	> 2700 mg/kg (Rabbit)	= 33 mg/L (Rat)4 h
Xylene 1330-20-7	3500 mg/kg (Rat)	1100 mg/kg (Rabbit)	6700 ppm (Rat)4 h
Titanium dioxide 13463-67-7	10000 mg/kg (Rat)	-	-
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h
Toluene 108-88-3	2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 28.1 mg/L (Rat)4 h

### 11.2 Information on toxicological effects

### Skin corrosion/irritation

Product Information • No information available <u>Component Information</u>

No information available

#### Serious eye damage/eye irritation

Product Information
No information available
Component Information
No information available

#### Respiratory or skin sensitization

<u>Product Information</u> • No information available <u>Component Information</u> • No information available

### Germ cell mutagenicity

Product Information • No information available <u>Component Information</u> • No information available

### Carcinogenicity

<u>Product Information</u>
The table below indicates whether each agency has listed any ingredient as a carcinogen <u>Component Information</u>
Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	
Titanium dioxide 13463-67-7	-	Group 2B	-	
Ethylbenzene 100-41-4	-	Group 2B	-	

### **Reproductive toxicity**

Product Information • No information available <u>Component Information</u> • No information available

**STOT - single exposure** No information available

**STOT - repeated exposure** No information available

### Other adverse effects

Product Information • No information available <u>Component Information</u> • No information available

### Aspiration hazard

Product Information • No information available <u>Component Information</u> • No information available

### 12. Ecological information

### 12.1 Toxicity

### Ecotoxicity

No information available

< 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Parachlorobenzotrifluoride 98-56-6	-	-	EC50: 48 h Daphnia magna 3.68 mg/L
Xylene	-	LC50: 96 h Pimephales promelas	EC50: 48 h water flea 3.82 mg/L
1330-20-7		13.4 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.661 - 4.093	LC50: 48 h Gammarus lacustris 0.6 mg/L
		mg/L static LC50: 96 h Oncorhynchus mykiss 13.5 - 17.3	
		mg/L LC50: 96 h Lepomis	
		macrochirus 13.1 - 16.5 mg/L flow-through LC50: 96 h Lepomis	
		macrochirus 19 mg/L LC50: 96 h Lepomis macrochirus 7.711 - 9.591	
		mg/L static LC50: 96 h Pimephales	
		promelas 23.53 - 29.97 mg/L static LC50: 96 h Cyprinus carpio 780	
		mg/L semi-static LC50: 96 h Cyprinus carpio 780 mg/L LC50: 96	
		h Poecilia reticulata 30.26 - 40.75	
		mg/L static	
Ethylbenzene 100-41-4	EC50: 72 h Pseudokirchneriella subcapitata 4.6 mg/L EC50: 96 h	LC50: 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L static LC50: 96 h	EC50: 48 h Daphnia magna 1.8 - 2.4 mg/L

	Pseudokirchneriella subcapitata 438	, , , ,	
	mg/L EC50: 72 h	semi-static LC50: 96 h Pimephales	
	Pseudokirchneriella subcapitata 2.6	promelas 7.55 - 11 mg/L	
	- 11.3 mg/L static EC50: 96 h	flow-through LC50: 96 h Lepomis	
	Pseudokirchneriella subcapitata 1.7	macrochirus 32 mg/L static LC50:	
	- 7.6 mg/L static	96 h Pimephales promelas 9.1 -	
		15.6 mg/L static LC50: 96 h Poecilia	
		reticulata 9.6 mg/L static	
Toluene	EC50: 96 h Pseudokirchneriella	LC50: 96 h Pimephales promelas	EC50: 48 h Daphnia magna 5.46 -
108-88-3	subcapitata 433 mg/L EC50: 72 h	15.22 - 19.05 mg/L flow-through	9.83 mg/L Static EC50: 48 h
	Pseudokirchneriella subcapitata	LC50: 96 h Pimephales promelas	Daphnia magna 11.5 mg/L
	12.5 mg/L static	12.6 mg/L static LC50: 96 h	
		Oncorhynchus mykiss 5.89 - 7.81	
		mg/L flow-through LC50: 96 h	
		Oncorhynchus mykiss 14.1 - 17.16	
		mg/L static LC50: 96 h	
		Oncorhynchus mykiss 5.8 mg/L	
		semi-static LC50: 96 h Lepomis	
		macrochirus 11.0 - 15.0 mg/L static	
		LC50: 96 h Oryzias latipes 54 mg/L	
		static LC50: 96 h Poecilia reticulata	
		28.2 mg/L semi-static LC50: 96 h	
		Poecilia reticulata 50.87 - 70.34	
		mg/L static	

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Parachlorobenzotrifluoride 98-56-6	3.7
Xylene 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.118
Toluene 108-88-3	2.65

### 12.4 Mobility in soil

No information available.

### 12.5 Other adverse effects

No information available

### **13. Disposal Considerations**

### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

### 14. Transport Information

Note	DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)"
DOT	Not regulated (If shipped in NON BULK packaging by ground transport)
MEX	no data available
IMDG UN	UN1263, Paint, 3, PGIII

#### IATA UN

UN1263, Paint, 3, PGIII

15. Regulatory information		
15.1 International Inventorie	<u>}</u>	
TSCA	Complies	
DSL	Complies	
EINECS/ELINCS	• ·	
ENCS		
IECSC	Complies	
KECL	Complies	
PICCS	- ·	
AICS	Complies	
NZIOC	- '	

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIOC - New Zealand Inventory of Chemicals

#### 15.2 U.S. Federal Regulations

### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %	Weight-%
Xylene 1330-20-7	1.0	5 - 10
Ethylbenzene 100-41-4	0.1	1 - 5

#### 15.3 Pesticide Information

#### Not applicable

### 15.4 U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
Crystalline silica (quartz) - 14808-60-7	Carcinogen
CUMENE - 98-82-8	Carcinogen

### 16. Other information

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal protection X

### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists) Ceiling (C) DOT (Department of Transportation) EPA (Environmental Protection Agency) IARC (International Agency for Research on Cancer) International Air Transport Association (IATA) International Maritime Dangerous Goods (IMDG) NIOSH (National Institute for Occupational Safety and Health) NTP (National Toxicology Program) OSHA (Occupational Safety and Health Administration of the US Department of Labor) PEL (Permissible Exposure Limit) Reportable Quantity (RQ) Skin designation (S\*) STEL (Short Term Exposure Limit) TLV® (Threshold Limit Value) TWA (time-weighted average)

### **Prepared By**

Kop-Coat, Inc. Regulatory Affairs 06-Sep-2018

Revision Date Revision Note No information available Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

### **End of Safety Data Sheet**